




## PDFNWB3.3x3.3-8L Plastic-Encapsulate MOSFETS

### **AB35N03 N-Channel Power MOSFET**

<b>V<sub>(BR)DSS</sub></b>	<b>R<sub>DS(on)</sub> TYP</b>	<b>I<sub>D</sub></b>
30 V	5.5mΩ@10V	35A
	8.5mΩ@4.5V	

#### **DESCRIPTION**

The AB35N03 uses advanced trench technology and design to provide excellent R<sub>DS(ON)</sub> with low gate charge. It can be used in a wide variety of applications



#### **FEATURES**

- High density cell design for ultra low R<sub>DS(ON)</sub>
- Fully characterized avalanche voltage and current
- Good stability and uniformity with high E<sub>AS</sub>
- Excellent package for good heat dissipation


#### **APPLICATIONS**

- High side switch in POL DC/DC converter
- Secondary side synchronous rectifier

AB  
35N03  
XX

PIN 1

AB35N03 = Part No.  
Solid dot = Pin1 indicator.  
XX = Code.



#### **ABSOLUTE MAXIMUM RATINGS (T<sub>a</sub>=25°C unless otherwise noted)**

Parameter	Symbol	Value	Unit
Drain-Source Voltage	V <sub>DS</sub>	30	V
Gate-Source Voltage	V <sub>GS</sub>	±20	V
Continuous Drain Current	I <sub>D</sub> <sup>①</sup>	35	A
Pulsed Drain Current	I <sub>DM</sub> <sup>②</sup>	120	A
Single Pulsed Avalanche Energy	E <sub>AS</sub> <sup>③</sup>	80	mJ
Maximum Power Dissipation	P <sub>D</sub> <sup>①</sup>	25	W
Thermal Resistance from Junction to Ambient	R <sub>θJA</sub> <sup>⑥</sup>	83.3	°C/W
Thermal Resistance from Junction to Case	R <sub>θJC</sub> <sup>①</sup>	5	°C/W
Operating Junction and Storage Temperature Range	T <sub>J</sub> , T <sub>stg</sub>	-55~+150	°C

## MOSFET ELECTRICAL CHARACTERISTICS







$T_a=25^\circ C$  unless otherwise specified

Parameter	Symbol	Test Condition	Min	Typ	Max	Unit
<b>Off characteristics</b>						
Drain-source breakdown voltage	$V_{(BR) DSS}$	$V_{GS} = 0V, I_D = 250\mu A$	30			V
Zero gate voltage drain current	$I_{DSS}$	$V_{DS} = 24V, T_J = 25^\circ C$			1.0	$\mu A$
		$V_{GS} = 0V, T_J = 125^\circ C$			100	
Gate-body leakage current	$I_{GSS}$	$V_{DS} = 0V, V_{GS} = \pm 20V$			$\pm 100$	nA
<b>On characteristics</b> <sup>④</sup>						
Gate-threshold voltage	$V_{GS(th)}$	$V_{DS} = V_{GS}, I_D = 250\mu A$	1.0	1.5	3.0	V
Static drain-source on-state resistance	$R_{DS(on)}$	$V_{GS} = 10V, I_D = 12A$		5.5	7.0	$m\Omega$
		$V_{GS} = 4.5V, I_D = 10A$		8.5	12	$m\Omega$
<b>Dynamic characteristics</b> <sup>④ ⑤</sup>						
Input capacitance	$C_{iss}$	$V_{DS} = 15V, V_{GS} = 0V, f = 1MHz$		1300	2600	$pF$
Output capacitance	$C_{oss}$			230	460	
Reverse transfer capacitance	$C_{rss}$			228	456	
Gate resistance	$R_g$	$f = 1MHz$		1.7		$\Omega$
<b>Switching characteristics</b> <sup>④ ⑤</sup>						
Total gate charge	$Q_g$	$V_{GS} = 10V, V_{DS} = 15V, I_D = 12A$		40	80	$nC$
Gate-source charge	$Q_{gs}$			5.1	10.2	
Gate-drain charge	$Q_{gd}$			9.1	18.2	
Turn-on delay time	$t_{d(on)}$	$V_{DS} = 15V, I_D = 12A$ $V_{GS} = 10V, R_G = 6\Omega$		9.0	18	$ns$
Turn-on rise time	$t_r$			26	50	
Turn-off delay time	$t_{d(off)}$			35	70	
Turn-off fall time	$t_f$			8.0	16	
<b>Drain-Source Diode Characteristics</b>						
Drain-source diode forward voltage	$V_{SD}$ <sup>④</sup>	$V_{GS} = 0V, I_S = 12A$			1.2	V
Continuous drain-source diode forward current	$I_S$ <sup>①</sup>				35	A
Pulsed drain-source diode forward current	$I_{SM}$ <sup>②</sup>				120	A



Notes:

1.  $T_C = 25^\circ C$  Limited only by maximum temperature allowed.
2.  $P_W \leq 10\mu s$ , Duty cycle  $\leq 1\%$ .
3. EAS condition:  $V_{DD} = 15V, V_{GS} = 10V, L = 0.1mH, R_g = 25\Omega$  Starting  $T_J = 25^\circ C$ .
4. Pulse Test : Pulse Width  $\leq 300\mu s$ , duty cycle  $\leq 2\%$ .
5. Guaranteed by design, not subject to production.
6. The value of  $R_{eJA}$  is measured with the device mounted on 1 in 2 FR-4 board with 2oz. Copper, in a still air environment with  $T_a = 25^\circ C$ .



# Typical Characteristics



## Typical Characteristics



## PDFNWB3.3x3.3-8L Package Outline Dimensions




Symbol

Dimensions In Millimeters

Dimensions In Inches

	Min.	Max.	Min.	Max.
A	0.650	0.850	0.026	0.033
A1	0.152 REF.		0.006 REF.	
A2	0~0.05		0~0.002	
D	2.900	3.100	0.114	0.122
D1	2.300	2.600	0.091	0.102
E	2.900	3.100	0.114	0.122
E1	3.150	3.450	0.124	0.136
E2	1.535	1.935	0.060	0.076
b	0.200	0.400	0.008	0.016
e	0.550	0.750	0.022	0.030
L	0.300	0.500	0.012	0.020
L1	0.180	0.480	0.007	0.019
L2	0~0.100		0~0.004	
L3	0~0.100		0~0.004	
H	0.315	0.515	0.012	0.020
$\theta$	9°	13°	9°	13°

## PDFNWB3.3x3.3-8L Suggested Pad Layout



Note:


1. Controlling dimension:in millimeters.

2.General tolerance: $\pm 0.05\text{mm}$ .

3.The pad layout is for reference purposes only.

# PDFNWB 3.3x3.3-8L Tape and Reel

## PDFNWB3.3x3.3-8L Embossed Carrier Tape



### Packaging Description:


**PDFNWB3.3x3.3-8L** parts are shipped in tape.

The carrier tape is made from a dissipative (carbon filled) polycarbonate resin. The cover tape is a multilayer film (Heat Activated Adhesive in nature) primarily composed of polyester film, adhesive layer, sealant, and anti-static sprayed agent. These reeled parts in standard option are shipped with 5,000 units per 13" or 33.0 cm diameter reel. The reels are clear in color and is made of polystyrene plastic (anti-static coated).


Dimensions are in millimeter

Pkg type	A	B	C	d	E	F	P0	P	P1	W
PDFNWB3.3x3.3-8L	3.55	3.55	1.10	Ø1.50	1.75	5.50	4.00	8.00	2.00	12.00

## PDFNWB3.3x3.3-8L Tape Leader and Trailer



## PDFNWB3.3x3.3-8L Reel



Dimensions are in millimeter

Reel Option	D	D1	D2	G	W1	W2
13" Dia	Ø330.00	100.00	13.00	1.90	17.60	12.40

REEL	Reel Size	Box	Box Size(mm)	Carton	Carton Size(mm)
5,000 pcs	13 inch	5,000 pcs	340×336×29	50,000 pcs	353×346×365